



INSTITUTE OF HEALTH & FAMILY WELFARE

(Department of Health and Family Welfare, Government of West Bengal)

29, GN BLOCK, SECTOR – V, BIDHAN NAGAR, KOLKATA – 700 091.

Phone No. : Tele Fax No. : 2357-8870,

E-mail: ihfwkolkata@gmail.com Website : www.ihfwkolkata.org

Memo No. IHFW/LCD Projector/132/2024/4633

Date : 16.01.2024

NOTICE

Sealed Quotations are invited from the bonafide Agencies for 1(One) LCD Projector with Ceiling Mount Bracket, HDMI to HDMI High-Speed Cable, 10.2 GBPS with Ethernet(10 mtr.) with Instalation (As per enclosed list) for 2nd Floor Conference Hall of the Institute of Health & Family Welfare, Kolkata . Last date of submission of the said quotation is 29.01.2024 upto 1 p.m. and will be opened on 29.01.2024 at 4 p.m. at the office chamber of the undersigned. Required documents to be submitted alongwith the Quotation are Trade Licence, PAN Card, I.T. Return receipt for the Assessment Year 2023 – 2024, and other relevant documents, if any.

Suparna Datta
16/1/24

(Prof. Dr. Suparna Datta)

Director,
IHFW, Kolkata.

Memo No. IHFW/LCD Projector/132/2024/4633/17) Date : 16.01.2024

Copy forwarded for information & necessary action to the :-

1. I.T. Cell, H & FW Dept. is requested to display the matter in the Health & Family Welfare Website
2. IHFW, Website
3. Notice Board, IHFW, Kolkata
4. DME, Deptt. of Health & Family Welfare, GoWB and Vice-Chairman, Governing Body, IHFW, Kolkata.
5. A.O., IHFW, Kolkata
6. Cash & Accounts Section, IHFW, Kolkata
7. Guard file

Suparna Datta
16/1/24

(Prof. Dr. Suparna Datta)

Director,
IHFW, Kolkata.

LCD Projectors Product Details:

KEY FEATURES

- LCD, 3,600 lumens, WXGA
- WXGA LCD Projector (3600 Lumens) & Wireless.
- 1280 x 800 pixels
- 16,000:1 contrast ratio
- Throw Distance: Min-2.5 Feet / Max- 20 Feet
- Ideal For: Education & Commercial

Detail Specifications:

Power consumption	300 W 6W when Standby mode set to Normal, 0.5W when Standby mode set to Eco*1 * Operating Temperature: 25°C (77°F), Altitude: 700m (2,297 ft), IEC62087: 2008 Broadcast contents, Picture mode: Dynamic
BTU value	Max 1,024BTU
LCD panel	Panel size :15.0 mm (0.59 inches) diagonal (16:10 aspect ratio) Display method: Translucent screen LCD panel 3 panels, 3 primary color system Pixels 1,024,000 pixels (1280 x 800 dots) x 3 panels Colors: Full color (16,777,216 colors)
Lens	Manual zoom: 1.2 x Manual focus: F = 1.6-1.76, f = 19.16 mm-23.02 mm
Throw ratio	1.48-1.78:1
Light output	3,600 lm (When [PICTURE MODE] is set to [DYNAMIC], [LAMP POWER] is set to [NORMAL], [AUTO POWER SAVE] is set to [OFF], and [DAYLIGHT VIEW] is set to [OFF])
Resolution	1280 x 800 pixels (Input signals that exceed this resolution will be converted to 1280 x 800 pixels.)
Contrast ratio	20,000:1 (When [PICTURE MODE] is set to [DYNAMIC], [LAMP POWER] is set to [NORMAL], [IRIS] is set to [ON], [AUTO POWER SAVE] is set to [OFF], and [DAYLIGHT VIEW] is set to [OFF])
Screen size	0.76-7.62 m (30-300 inches) diagonally, 16:10 aspect ratio
Network	Rj 45 and Wireless
Minimum Input (Terminals)	COMPUTER 1 IN, COMPUTER 1 OUT (1 (High-density D-sub 15 pin female), HDMI IN X 2, AUDIO IN 1, AUDIO OUT (M3 stereo mini jack, stereo monitor output compatible, 0 V [rms] to 2.0 V [rms] variable, output impedance 2.2 kΩ and less), USB, LAN
Wireless	Wireless module compatible on this Projector
Built-in speaker	10 W (monaural) x 1

Additional accessories:

1. Ceiling Mount Bracket
2. HDMI to HDMI High Speed HDMI Cable 10.2GBPS with Ethernet.